

Product Description

Duratex is a highly reactive petroleum based chemically softening compound designed to remove early concrete build-up from forming hardware, equipment, ready-mix chutes, and other construction machinery coming in contact with concrete.

General Uses

Duratex prevents and removes early concrete build-up on concrete forms, tools, mixers, hardware, shoring and scaffolding equipment, ready-mix truck chutes, mortar mixers, aluminum forms and post tensions rods. Coat equipment with Duratex prior to use and again before cleaning or storing.

Features

- VOC compliant – Federal standards
- Softens concrete build-up for easier removal
- Coats steel, aluminum and other alloy metals to prevent concrete bonding
- Prevents rust build up on steel forms & equipment
- Use as a release agent on residential aluminum forms where mix designs containing greater than 20% fly ash
- Prevent concrete build-up by applying a preventive treatment prior to equipment & form use

Instructions for use

Lightly spray Duratex over the interior of concrete mixers after clean out to prevent concrete bonding. Duratex, over time, will soften and remove hardened concrete. Forming hardware with concrete build-up should be sealed in Duratex until the build-up becomes soft and easy to remove.

Packaging

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

Storage and Handling

Duratex should be stored indoors and, when left in its original unopened package will maintain its designed performance for 12 months.

Limitations/Warnings

- Do not over apply.
- Do not use as a bondbreaker for tilt-up construction.
- Do not use on Styrofoam or latex molds.
- Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of Duratex.

Health Warning

Combustible... Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame. Refer to Safety Data Sheet before use.

VOC content: less than 250 g/L. Complies with USA and Federal AIM VOC standards. Do not thin or dilute.

Limited Warranty: Subject to the conditions and limitations stated below, M-Chem Solutions LLC ("M-Chem") warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product. As conditions of this limited warranty, you may be required. At the option of M-Chem to provide proof of product purchase and use. DISCLAIMER: THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. EXCLUSIVE REMEDY: The sale and exclusive remedy for a breach of this limited warranty is replacement of the M-Chem product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of M-Chem is limited to return of the original purchase price. EXCLUSION: M-Chem is not responsible for workmanship not in accordance with M-Chem instructions and industry standard guidelines. M-Chem IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.
