

## PRODUCT DESCRIPTION

A high quality, clean, odorless, chemically active, environmentally friendly form release agent. Formulated with non-vegetable environmentally friendly materials to provide the concrete construction forming industry with bio friendly release agent for both indoor and outdoor application. Green Release produces a smooth, void free, architectural concrete surface. VOC compliant.

## GENERAL USES

Green Release will aid in the release of the form from hardened concrete on the widest range of forming materials. Green Release will help eliminate the problems associated with soil & water contaminations from the commercial jobsite. Ideal for both interior and exterior concrete forming applications including precast applications.

## FEATURES

- Ensure easy stripping of forms
- Produces smooth natural architectural surfaces chemical action is not harmful to the concrete surface
- Will not retard, etch or soften concrete surface, even if over applied
- Run-down is reduced and reinforcing steel stays cleaner
- Has a positive release that keeps forms clean-no cleaning between pours is necessary
- Repeated use makes wood forms water repellent and extends their useful life
- Inhibits rust formation on steel forms
- Easy to apply, brush, spray or roll
- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants
- Reduces bug holes and extend the life of most forming materials
- Keeps workers clean and odor free on and off job site

## STANDARDS

Meets the requirements LEED® EQ Credit 4.2 Low Emitting Materials: Paints & Coatings .

**Mn DOT approved.**

## INSTRUCTIONS FOR USE

Green Release should be applied in a thin uniform film with a sprayer, brush, or roller. No special application equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided. Form surfaces should be clean of dirt, rust, scale and concrete build up prior to application.

**Specific applications are as follows:**

### **2000 sq.ft. per U.S. gallon on:**

- Fiberglass
- Plastic
- Steel □
- Aluminum
- High density, overlaid plywood
- Elastomeric formliners

### **1000 sq.ft. per U.S. gallon on:**

- Medium density, overlaid plywood
- Urethane coated plywood
- Coated paper forms

### **750 sq.ft. per U.S. gallon on:**

- Dimensional lumber
- Rough sawn lumber
- Striated plywood

## PACKAGING

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

## LIMITATIONS/WARNINGS

- Do not over apply
- Do not use as a bondbreaker for tilt-up construction □
- Do not use on plaster molds unless coated with a suitable sealer
- Colder temperatures will increase the viscosity of Green Release

---

Limited Warranty: Subject to the conditions and limitations stated below, M-Chem Solutions LLC ("M-Chem") warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product. As conditions of this limited warranty, you may be required. At the option of M-Chem to provide proof of product purchase and use. DISCLAIMER: THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. EXCLUSIVE REMEDY: The sale and exclusive remedy for a breach of this limited warranty is replacement of the M-Chem product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of M-Chem is limited to return of the original purchase price. EXCLUSION: M-Chem is not responsible for workmanship not in accordance with M-Chem instructions and industry standard guidelines. M-Chem IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

---