

## Product Description

A premium, chemically active, highly refined petroleum based form release agent formulated for use on Styrofoam, plastic, resin, & elastomeric form-liners. MP Elastomeric is formulated without diesel fuel and other common lubricating oils. MP Elastomeric produces a smooth, void free, architectural concrete surface. VOC compliant.

## General Uses

MP Elastomeric will aid in the release of the Styrofoam, plastic, resin & elastomeric form-liners from hardened concrete.

## Features

- Ensures easy stripping of forms
- Produces smooth natural architectural surfaces chemical action is not harmful to the concrete surface
- Will not retard, etch, or soften concrete surfaces, even if over applied
- May be used on concrete structures that will store potable water
- Has a positive release that keeps forms clean, no cleaning between pours is necessary
- Easy to apply with brush, sprayer or roller
- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants
- Keeps workers clean and odor free on and off the job site

## Standards

Meets the requirements of Corps of Engineers Specifications CW 03101, section 2.1.2. VOC

## Instructions for Use

MP Elastomeric should be applied in a thin uniform film with a sprayer, brush or roller. No special application equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided. Form surfaces should be clean of dirt, rust, scale and concrete build up prior to application.

## Specific applications are as follows:

### **Patterned face:**

1000 - 1500 sq. ft. per U.S. gallon

## Packaging

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums □
- gallon (18.9 L) pails

## Limitations/Warning

- Do not over apply.
- Do not use as a bond breaker for tilt-up construction.
- Colder temperatures will increase the viscosity of MP Elastomeric

## Health Warning

Combustible... Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame. Refer to Safety Data Sheet before use.

**VOC content:** less than 250 g/L. Complies with USA and Federal AIM VOC standards. Do not thin or dilute.

---

Limited Warranty: Subject to the conditions and limitations stated below, M-Chem Solutions LLC ("M-Chem") warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product. As conditions of this limited warranty, you may be required. At the option of M-Chem to provide proof of product purchase and use. DISCLAIMER: THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. EXCLUSIVE REMEDY: The sale and exclusive remedy for a breach of this limited warranty is replacement of the M-Chem product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of M-Chem is limited to return of the original purchase price. EXCLUSION: M-Chem is not responsible for workmanship not in accordance with M-Chem instructions and industry standard guidelines. M-Chem IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

---