

Product Description

Plyform Sealer is an oil free, high solids, ready-to-use moisture cured polyurethane sealer coating designed to protect new BB grade plyform forming systems. Plyform Sealer tightly adheres to plyform surfaces forming a water and alkali proof, abrasion resistant, tough and flexible film. Plyform Sealer extends the usable life and reduces plyform deterioration.

General Uses

Plyform Sealer is a ready-to-use sealer that can be applied by roller or brush. The hardened film seals the surfaces to protect the forms from the penetration of water from the concrete and the alkali attack on the wood fibers. This positive sealing quality assures up to three times the life to plyform while preventing the transfer of wood grain marks to concrete surfaces. Plyform Sealer treated plyform assure smooth, stain and residual free concrete. The resulting residual-free concrete surfaces are ready to receive paints, moisture proofing, damp proofing coatings and other treatments.

Features

Develops a tough protective film to extend plyform life
Water-tight to prevent moisture intrusion into plyform
VOC compliant
Fast drying

Instructions for Use

New forms

Clean before application with Solvent 100. Do not apply over freshly oiled forms. Apply evenly by brush or lamb wool applicator at the rate of 300 sq. ft. per gallon. If a higher film build-up is desired, apply a second coat at the rate of 500 sq. ft. per gallon within 24 hours to assure positive adhesion to first coat. After 24 hours, sand sealed surfaces prior to application of Plyform Sealer for best inter coat adhesion.

Used forms: Not designed for use.

Packaging

- 5 gallon (18.9 L) pails

Limitations/Warning

- Do not over apply.
- Do not use as a bondbreaker for tilt-up construction.
- Do not use on Styrofoam or latex molds. Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of Plyform Sealer.

Health Warning

Combustible... Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame. Refer to Safety Data Sheet before use.

VOC content: less than 600 g/L. Complies with USA and Federal AIM VOC standards. Do not thin or dilute.

Limited Warranty: Subject to the conditions and limitations stated below, M-Chem Solutions LLC ("M-Chem") warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product. As conditions of this limited warranty, you may be required. At the option of M-Chem to provide proof of product purchase and use. DISCLAIMER: THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. EXCLUSIVE REMEDY: The sale and exclusive remedy for a breach of this limited warranty is replacement of the M-Chem product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of M-Chem is limited to return of the original purchase price. EXCLUSION: M-Chem is not responsible for workmanship not in accordance with M-Chem instructions and industry standard guidelines. M-Chem IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.
